

# AEOLUS-SV12-6L2C



- 12th-14th Gen Intel® Core™ i7/i5/i3 with Desktop-grade Intel® H610 chipset, support processor up to 65W TDP;
- Comes with On board 6 channels Gigabit LAN, supports Wake-on-LAN, PXE;
- Supports 4G/WIFI wireless internet access and enables wireless remote control assistance in various environments;
- 2\*RS232/RS485 (Switchable via DIP switches or BIOS);
- Equipped with HDMI/DP interfaces, Sync/Async HD video output supported;
- Supports DC 12V-24V power supply with resistance to current interference;
- Supports multiple installation methods: wall-mounted, vertical, and DIN rail mounting
- Adopts open grille with built-in cooling fans & copper tube heat dissipation system, ensuring excellent heat dissipation performance;




The actual appearance is subject to the final configuration.

## Specifications

<b>Model</b>	AEOLUS-SV12-6L2C	
<b>Supported OS</b>	Win 10, Win 11, Linux (Ubuntu, Dbian, Kali, CentOS), Win 10 IoT	
<b>Chipset</b>	Model	Intel® H610 Chipset, TDP 6W
	Intel VT-d	Supported
<b>CPU</b>	Socket	Intel® Desktop Processors Socket LGA1700
	Series	12th-14th Gen. Intel® Core™ i7/ i5 /i3 Processor
	TDP	Up to 65W
	Graphic	Intel® UHD Graphics (depends on processor model)
	BIOS	AMI UEFI BIOS
<b>RAM</b>	SO-DIMM	2* DDR4 3200 MHz SO-DIMM Socket, Capacity up to 64GB;
<b>Storage Device</b>	M.2	1* M.2 (NGFF) 2280 M-key slot, support SATA3.0 (6Gps) SSD
<b>I/O Interface</b>	COM	2* RS232/RS485, switchable via switches or BIOS
	Ethernet	5* Intel i210-AT GbE LAN, 1* Intel i219-V GbE LAN; Supports wake-on-LAN, PXE
	USB	4* USB 3.2; 1* Internal USB 2.0; 2* 4-Pin USB 2.0 internal header
	Video	1* HDMI (Max Resolution: 4096x2160 @30Hz); 1* DP (Max Resolution: 4096x2160 @30Hz);
	SIM	1* Nano SIM connected to Mini-pcie, support 4G wireless
	Power Supply	DC 12V-24V, Auto detected, support RVP/OVP/OCP; 2* 2-PIN green connector, 5.08mm
	Featured Interface	1* Clear CMOS; 1* Recovery Button;
<b>Extended Capabilities</b>	Additional	1* Full Size Mini-PCIe slot (PCIe x1 GEN3), optional CAN/LAN/WiFi ect.
	Internal Interface	1* Full Size Mini-PCIe (USB2.0), support 4G;
<b>Environment</b>	Operating Temp.	-10 ~ 60 °C w/ 0.7m/s Airflow
	Storage Temp.	-40 ~ 85 °C (-40~185 °F)
	Relative Humidity	40 °C @95%, Non-Condensing
<b>Physical Characteristics</b>	Dimensions	215* 57.1* 166.8 mm (W* H* D)
	Net Weight	2.20 KG
<b>Regulation</b>	EMC	CE/FCC Class B, CCC
	Safety	CE-LVD, RoHS, CCC


Dimension

Unit:mm



The actual appearance and dimensions are subject to the final configuration

Front Panel External IO Mechanical Layout/Drawing



Ordering Information

SO-DIMM Socket	M.2 2280 M-key Slot	Full Size Mini-PCIe	RS232/RS485 switchable	GbE LAN	Nano SIM Card Slot	Clear CMOS
2	1	2	2	6	1	1
USB3.2	USB2.0 Header	Internal USB 2.0 (4-Pin)	HDMI	DP	Remote Switch Button	Power Supply
4	2	2	1	1	1	DC 12V-24V

Processors Info & Available List

CPU	Code Name	Total Cores	Total Threads	Max Turbo Frequency	Base Frequency	Cache	TDP	Memory Types	Integrated Graphics
Intel® Core™ i3-12100	Alder Lake	4	8	4.30 GHz	3.30 GHz	12 MB Intel® Smart Cache	60W	DDR4	Intel® UHD Graphics 730
Intel® Core™ i5-12400	Alder Lake	6	12	4.40 GHz	2.50 GHz	18 MB Intel® Smart Cache	65W	DDR4	Intel® UHD Graphics 730
Intel® Core™ i7-12700	Alder Lake	12	20	4.90 GHz	2.10 GHz	25 MB Intel® Smart Cache	65W	DDR4	Intel® UHD Graphics 770
Intel® Core™ i9-12900	Alder Lake	16	24	5.10 GHz	2.40 GHz	30 MB Intel® Smart Cache	65W	DDR4	Intel® UHD Graphics 770
Intel® Core™ i3-13100	Alder Lake	4	8	4.50 GHz	3.40 GHz	12 MB Intel® Smart Cache	60W	DDR4	Intel® UHD Graphics 730
Intel® Core™ i5-13400	Alder Lake	10	16	4.60 GHz	2.50 GHz	20 MB Intel® Smart Cache	65W	DDR4	Intel® UHD Graphics 730
Intel® Core™ i7-13700	Alder Lake	16	24	5.20 GHz	2.10 GHz	30 MB Intel® Smart Cache	65W	DDR4	Intel® UHD Graphics 770
Intel® Core™ i3-14100	Alder Lake	4	8	4.70 GHz	3.50 GHz	12 MB Intel® Smart Cache	60W	DDR4	Intel® UHD Graphics 730
Intel® Core™ i5-14400	Alder Lake	10	16	4.70 GHz	2.50 GHz	20 MB Intel® Smart Cache	65W	DDR4	Intel® UHD Graphics 730
Intel® Core™ i7-14700	Alder Lake	20	28	5.40 GHz	2.10 GHz	33 MB Intel® Smart Cache	65W	DDR4	Intel® UHD Graphics 770

All products and company name listed are trademarks or trade names of their respective companies.

**Packing list**

Default Items	Qty
AEOLUS-SV12-6L2C Unit	1
Wall-mounted bracket	1
AC-to-DC Adapter	1
Power cable 3-pin 150cm	1

**Options for default items**

Optional Items	Qty
Power cable 3-pin 150cm, USA type	-
Power cable 3-pin 150cm, EU type	-
Power cable 3-pin 150cm, UK type	-

**Optional accessories or internal modules for unit**

Optional Items	Max Qty	Description
4G Module	1	Connected by Mini-PCIe interface
WiFi Module without AP mode	1	Connected by Mini-PCIe interface
EtherCAT	1	EtherCAT Master, supporting a maximum of 16 slaves (servos + I/O) at a 1ms cycle

!! Note: As this product has expansion slots, please consult sales for the specific maximum number of expandable interfaces.